

在 庫 表

ガス管/白ガス管(熔協品) = 配管用炭素鋼鋼管(SGP)							
呼び径	外径×肉厚 mm	kg/m	kg/5.5m	黒無	黒付	白無	白付
6A	1/8B	10.5×2.0	0.419	2.30	●		
8A	1/4B	13.8×2.3	0.652	3.59	●	●	●
10A	3/8B	17.3×2.3	0.851	4.68	●	●	●
15A	1/2B	21.7×2.8	1.31	7.20	●	●	●
20A	3/4B	27.2×2.8	1.68	9.24	●	●	●
25A	1B	34.0×3.2	2.43	13.4	●	●	●
32A	1-1/4B	42.7×3.5	3.38	18.6	●	●	●
40A	1-1/2B	48.6×3.5	3.89	21.4	●	●	●
50A	2B	60.5×3.8	5.31	29.2	●	●	●
65A	2-1/2B	76.3×4.2	7.47	41.1	●	●	●
80A	3B	89.1×4.2	8.79	48.3	●	●	●
90A	3-1/2B	101.6×4.2	10.1	55.6	●	*	*
100A	4B	114.3×4.5	12.2	67.1	●	●	●
125A	5B	139.8×4.5	15.0	82.5	●	●	●
150A	6B	165.2×5.0	19.8	109	●	●	●
175A	7B	190.7×5.3	24.2	133	●	●	
200A	8B	216.3×5.8	30.1	166	●	*	*
250A	10B	267.4×6.6	42.4	233	●	*	*
300A	12B	318.5×6.9	53.0	292	●	*	*
350A	14B	355.6×7.9	67.7	372	●	●	
400A	16B	406.4×7.9	77.6	427	●	●	
450A	18B	457.2×7.9	87.5	481			
500A	20B	508.0×7.9	97.4	536			

ガス管在庫品長さ 5.5m ●印=常時在庫品 *印=受注製作品

STK/白STK (一般構造用炭素鋼鋼管: STK400)					
外径×肉厚	長さ	kg/m	Kg/1本	黒	白
21.7X1.9	5.5	0.928	5.10	●	
X2.3	5.5	1.10	6.05	●	
27.2X1.9	5.5	1.19	6.54	●	
X2.3	5.5	1.41	7.76	●	●
34.0X2.3	5.5	1.80	9.90	●	●
42.7X2.3	5.5	2.29	12.6	●	●
48.6X2.3	5.5	2.63	14.5	●	●
X3.2	6.0	3.58	21.5	●	●
60.5X2.3	5.5	3.30	18.2	●	●
X3.2	6.0	4.52	27.1	●	●
76.3X2.8	5.5	5.08	27.9	●	●
X3.2	6.0	5.77	34.6	●	●
89.1X2.8	5.5	5.96	32.8	●	●
X3.2	6.0	6.78	40.7	●	●
101.6X3.2	6.0	7.76	46.6	●	●
114.3X3.5	5.5	9.56	52.6	●	●
139.8X3.5	5.5	11.8	64.9	●	●
165.2X3.7	5.5	14.7	80.8	●	●
216.3X4.5	5.5	23.5	129	●	*

STKM11A (機械構造用炭素鋼鋼管)			
外径×肉厚	長さm	kg/m	kg/1本
6.0X1.0	3.66	0.123	0.45
8.0X1.0	3.66	0.173	0.633
9.0X1.0	3.66	0.197	0.721
10.0X1.0	3.66	0.222	0.813
12.0X1.0	3.66	0.271	0.992
12.7X1.0	3.66	0.289	1.06
X1.2	5.5	0.340	1.87
X1.6	5.5	0.438	2.41
15.9X1.2	5.5	0.435	2.39
X1.6	5.5	0.564	3.10
X2.0	5.5	0.686	3.77
19.1X1.2	5.5	0.530	2.92
X1.6	5.5	0.690	3.80
X2.0	5.5	0.843	4.64
22.2X1.2	5.5	0.621	3.42
X1.6	5.5	0.813	4.47
X2.0	5.5	0.996	5.48
25.4X1.2	5.5	0.716	3.94
X1.6	5.5	0.939	5.16
X2.0	5.5	1.15	6.32
X2.3	5.5	1.31	7.20
27.2X1.6	5.5	1.01	5.56
28.6X1.2	5.5	0.811	4.46
X1.6	5.5	1.07	5.88
X2.0	5.5	1.31	7.20
31.8X1.2	5.5	0.906	4.98
X1.6	5.5	1.19	6.54
X2.0	5.5	1.47	8.08
X2.3	5.5	1.67	9.18
34.0X1.6	5.5	1.28	7.04
38.1X1.2	5.5	1.09	6.00
X1.6	5.5	1.44	7.92
X2.0	5.5	1.78	9.79
X2.3	5.5	2.03	11.2
42.7X1.6	5.5	1.62	8.91
45.0X1.6	5.5	1.71	9.40
48.6X1.6	5.5	1.85	10.2
50.8X1.6	5.5	1.94	10.7
X2.0	5.5	2.41	13.3
54.0X1.6	5.5	2.07	11.4
60.5X1.6	5.5	2.32	12.8
63.5X1.6	5.5	2.44	13.4
76.3X1.6	5.5	2.95	16.2
X2.0	5.5	3.66	20.1

プレジंक/ポストジंक			
外径×肉厚	長さm	kg/m	kg/1本
21.7X1.9	6.0	0.928	5.57
27.2X1.9	6.0	1.19	7.14
X2.3	6.0	1.41	8.46
34.0X2.3	6.0	1.80	10.8
X3.2	5.5	2.43	13.4
42.7X2.3	6.0	2.29	13.7
X3.5	5.5	3.38	18.6
48.6X2.3	6.0	2.63	15.8
60.5X2.3	6.0	3.30	19.8
76.3X2.8	6.0	5.08	30.5
15.9X1.6	5.5	0.564	3.10
19.1X1.6	5.5	0.690	3.80
25.4X1.6	5.5	0.939	5.16
31.8X1.6	5.5	1.19	6.54
38.1X1.6	5.5	1.44	7.92



〒279-0024 千葉県浦安市港20番地

asp1@abe-steelpipes.co.jp

TEL: 047-351-3211

FAX: 047-351-3213